



VIVAfloors

Projecten - Projects - Objekte **5000**

Projecten - Projects - Objekte

Specificaties - Specifications - Technische Daten

| NL | EN | DU | | Lijmversie Glue down Kleber | Clickversie Click Klick |
|--------------------------------------|---|------------------------------------|-----------------------|--|--|
| Specificaties | Specifications | Technische Daten | | | |
| Totale dikte | Total Thickness | Gesamtstärke | EN 428 | 2,5 mm | 5 mm <i>Inclusief ondervloer</i> <i>Subfloor included</i> <i>Inklusive Uterlage</i> |
| Dikte van de slijtlaag | Wear layer | Nutzschicht | EN 429 | 0,55 mm | 0,55 mm |
| Dikte geluiddempende IXPE ondervloer | Thickness soundinsulating IXPE underlay | Stärke trittschall IXPE untergrund | - | - | 0,6 mm |
| Totaal gewicht | Total Weight | Total Gewicht | EN 430 | 4,53 kg/m ² | 8,8 kg/m ² |
| Toplaag | Surface treatment | Oberflächenvergütung | Embossed | PUR | PUR |
| Afmeting | Dimension | Abmessung | EN 24342 | 5100 - 5800 only available in glue down: 121,9 x 22,8 cm | 5001 - 5004 only available in click: 122 x 22,5 cm |
| Gebruikscategorie | Usage classification | Klassifizierung | EN 685 | 32-41 | 32-41 |
| Clickverbinding | Locking System | Klickverbinding | | | 2G-2G Välinge |
| Testresultaten | Test Results | Testergebnisse | | | |
| Vloerverwarming | Underfloor heating | Fussbodenheizung | EN 12524 | Suitable Max 27 °C | Suitable Max 27 °C |
| Warmte doorlaat weerstand | Thermal resistance | Wärmedurchlasswiderstand | EN 12667 | 0,015 m ² K/W | 0,038 m ² K/W |
| Rolstoeltest | Castor Chair | Rollstuhl | EN 425 | Pass | Pass |
| Brandklasse | Fire resistance | Brandverhalten | EN 13501-1 | Bfl-s1 | Bfl-s1 |
| Weerstand chemische stoffen | Chemical resistance | Chemikalienbeständigkeit | EN 423 | Good | Good |
| Restindruk | Residual indentation | Eindruckverhalten | EN ISO 24343-1 | ≤ 0,10 mm | ≤ 0,15 mm |
| Slijptest | Slip resistance | Rutschhemmung | EN 13893 | R9 | R9 |
| Krasvastheid | Abrasion class | Verschleißgruppe | EN 660-2 | T | T |
| Geluidsabsorptie | Sound reduction | Reduzierung des Trittschalls | EN 717-2 ISO 10140 | 4 dB | 19 dB EU-norm 5 dB NL-norm <i>(incl Secura LVT Click Smart ISO 10140 Delta Lin 10 dB.)</i> |
| Lichtechtheid | Light stability | Lichtechtheit | ISO 105-B02 | Pass ≥ 6 | Pass ≥ 6 |
| Dimensionale stabiliteit | Dimensional stability | Massänderung | EN 23999 | < 0,25% | < 0,15% |
| Afmeting | Dimension | Verlegemass | EN427 | Pass | Pass |
| Toxiciteit | Toxic elements test | Toxicität | EN 71 | Not toxic | Not toxic |
| Garantie | Warranty | Garantie | | Residential 25 years Commercial 10 years | Residential 25 years Commercial 10 years |



IAC Gold gecertificeerd

IAC Gold certified

IAC Gold zertifiziert