



VAYA 291 AVUS FAST2FIX ECKIG

Samtgrau, Graphitschwarz, Kaschmirgrau, Gold Matt
Schnellmontage

GRIFFWERK Zink Türdrückergarnitur geeignet für den Einsatz im Privat- und Objektbereich, geprüft nach DIN EN 1906

- Griff mit fast2fix-Schnellmontage
- Lagerung: Griff lose, von Rosette getrennt
- Rosettenstärke: 6 mm
- Befestigung Griffrosetten: verdeckt mit M4-Verschraubung
- Befestigung Schlüsselrosetten: verdeckt mit Mehrzweckschrauben
- Standardtürstärke 38-50 mm
- Mit zusätzlichem Verlängerungsset bis Türstärke 80 mm möglich
- Hochhaltefedern auf beiden Griffseiten (Druckfedertechnik)
- Montage-/ Demontageöffnungen von unten, nicht im Sichtbereich
- Wartungsfreie Gleitlager für eine dauerhafte, geschmeidige und geräuschlose Funktion
- Auch mit smart2lock Verriegelung im Griff erhältlich
- Griffe kombinierbar mit Sicherheitsbeschlägen, Glastürschlössern und Fenstergriffen
- Gebrauchs-Kategorie 3|7|-|0|0|3|0|B (Buntbart, Profilzylinder, WC, OS, Wechselgarnitur)




Schloßkasten PURISTO S*
Edelstahl matt mit
Drücker VAYA 291 AVUS

Glass-door lock PURISTO S*
satin stainless steel
with lever VAYA 291 AVUS



Kombischutzbeschlag
TITANO SB_882
außen: Langschild
mit Kernziehschutz,
innen: Kombi-Rosettensatz

Combined security fitting
TITANO SB_882
outside: longplate with
key-rose anti-tamper,
inside: combined rose set



Fenstergriff
unverschießbar



Window levers
non-lockable

VAYA 291 AVUS FAST2FIX SQUARE

velvet grey, graphit black, cashmere grey, gold matt
Quick mounting


GRIFFWERK zinc lever handle set suitable for use in the private and commercial sector, tested to DIN EN 1906

- Handle with fast2fix quick mounting
- Storage: Handle loose, separate from rosette
- Rosette thickness: 6 mm
- Fixing handle rosettes: concealed with M4 screw fitting
- Fastening of key rosettes: concealed with multi-purpose screws
- Standard door thickness 38-50 mm
- With additional extension set up to door thickness 80 mm possible
- Hold-up springs on both sides of the handle (compression spring technology)
- Assembly/disassembly openings from below, not in the visible area
- Maintenance-free slide bearings for durable, smooth and noiseless operation
- Also available with smart2lock locking mechanism in the handle
- Handles can be combined with security fittings, glass door locks and window handles
- Usage category 3|7|-|0|0|3|0|B (key hole, euro profile, WC, OS, interchangeable fitting)



Wechselgarnitur PZ
mit Knopf Square

Rose change set
euro profile
with knob Square



Buntbart BB
Profilzylinder PZ
Standard WC
Rosette Form B

key hole
euro profile
WC/bath standard
Rose type B